

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

NOTICE OF ACCEPTANCE (NOA)

Roatan Mahogany USA, Inc. 4004 C Aurora Street Coral Gables, FL 33146

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "Roatan Mahogany" Outswing Wood Casement Window - L.M.I.

APPROVAL DOCUMENT: Drawing No. **15-254**, titled "Mahogany Casement Windows", sheets 1 through 7 of 7, dated 08/26/15, prepared by EngCo, Inc., signed and sealed by Pedro M. De Figueiredo, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant Limitations:

- 1. Installation into CMU not permitted at head and sill.
- 2. Concrete shall be minimum 3000 psi.
- 3. Hollow block shall conform to ASTM C-90, with a minimum compressive strength of 2,000 psi.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.



NOA No. 15-0921.09 Expiration Date: August 08, 2019 Approval Date: May 5, 2016 Page 1



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 T (786) 315-2590 F (786) 315-2599 www.miamidade.gov/economy

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA# 14-0722.09 and consists of page 1, this page 2, and evidence pages E-1, E-2 and E-3, as well as approval document mentioned above.

The submitted documentation was reviewed by Jorge M. Plasencia, P.E.



NOA No. 15-0921.09 Expiration Date: August 8, 2019 Approval Date: May 5, 2016

Page 2

Roatan Mahogany USA, Inc.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No. 15-254, titled "Mahogany Casement Windows", sheets 1 through 7 of 7, dated 08/26/15, prepared by EngCo, Inc., signed and sealed by Pedro M. De Figueiredo, P.E.

B. TESTS

- 1. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. HETI-01-1006, dated 10/26/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)
- 2. Test reports on: 1) Air Infiltration Test, per FBC TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC TAS 202-94 along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1184**, dated 10/29/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)
- 3. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. HETI-01-1095, dated 11/02/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)
- 4. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 - 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 3) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94
 - along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1077**, dated 09/09/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)
- 5. Test reports on: 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 2) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94 along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1190**, dated 09/25/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)

Jorge M. Plasencia, P.E. Product Control Unit Supervisor NOA No. 15-0921.09

Expiration Date: August 08, 2019 Approval Date: May 05, 2016

Roatan Mahogany USA, Inc.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

B. TESTS (CONTINUED)

- 6. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 - 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 3) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1079**, dated 09/26/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)

- 7. Test reports on: 1) Air Infiltration Test, per FBC TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC TAS 202-94

along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1185**, dated 04/18/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)

- 8. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 - 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1007**, dated 09/06/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)
- 9. Test reports on: 1) Air Infiltration Test,
 - 2) Uniform Static Air Pressure Test,
 - 3) Water Resistance Test

along with marked-up drawings and installation diagram of an outswing wood casement window, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-01-1186**, dated 04/18/01, signed and sealed by Hector M. Medina, P.E. (Submitted under NOA# 02-0510.03)

10. Inspection reports on: 1) Sealant by Dow Corning 995, along with marked-up drawings and installation diagram, prepared by Hurricane Engineering & Testing, Inc., for Test Reports No. HETI-01-1190, HETI-01-1077, HETI-01-1095, HETI-01-1 1184, HETI-01-1079, HETI-01-1185, HETI-01-1007, HETI-01-1186, and HETI-01-1006, dated 06/28/02, signed and sealed by Rafael E. Droz-Seda, P.E. (Submitted under NOA# 02-0510.03)

C. CALCULATIONS

1. Anchor verification calculations and structural analysis, complying with FBC-2014, prepared by EngCo, Inc., dated 04/21/16, signed and sealed by Pedro M. De Figueiredo, P.E.

2. Glazing complies with ASTM E1300-04.

Froduct Control Unit Supervisor NOA No. 15-0921.09

Expiration Date: August 08, 2019 Approval Date: May 05, 2016

Roatan Mahogany USA, Inc.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

D. QUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER)

E. MATERIAL CERTIFICATIONS

1. Notice of Acceptance No. 13-0909.10 issued to Polymer Extrusion Technology, Inc. dba Glasslam for their "Glasslam Safety-Plus II Glass Interlayer" dated 10/03/13, expiring on 08/07/18.

F. STATEMENTS

- 1. Statement letter of conformance, complying with FBC-2014, and of no financial interest, dated 08/26/15, issued by EngCo Inc., signed and sealed by Pedro M. De Figueiredo, P.E.
- 2. Bill of Sale document, dated 09/26/13, between Roatan Mahogany Millwork, Inc., seller and Roatan Mahogany USA, Inc., buyer, signed by Robert De Leon. (Submitted under NOA# 14-0722.09)

G. OTHER

1. Notice of Acceptance No. 14-0722.09, issued to Roatan Mahogany USA, Inc. for their Series "Roatan Mahogany" Outswing Wood Casement Window – L.M.I., approved on 09/04/14 and expiring on 08/08/19.

Jorge M. Plasencia, P.E. Product Control Unit Supervisor NOA No. 15-0921.09

Expiration Date: August 08, 2019 Approval Date: May 05, 2016

GENERAL NOTES:

FLORIDA BUILDING CODE 2014 HVHZ LARGE & SMALL MISSILE IMPACT RATED

- I DEFINITION: THIS PRODUCT IS A CASEMENT MAHOGANY WINDOW; DESIGNED, CONTRUCTED AND ERECTED TO ENCLOSE AN AREA. PROVIDING PROTECTION FROM HURRICANE FORCE WINDS WITHIN THE ALLOWABLE DESIGNED PRESSURES AND LIMITATIONS STATED IN THIS APPROVAL.
- 2- CODE: THIS PRODUCT HAS BEEN TESTED AND DESIGNED IN ACCORDANCE WITH THE 2014 FLORIDA BUILDING CODE, HIGH VELOCITY HURRICANE ZONES (HVHZ).
- 3- POSTING: A PERMANENT LEGIBLE DECAL SHALL BE PLACED AT A READILY VISIBLE LOCATION STATING THE FOLLOWING:


"ROATAN MAHOGANY USA, INC.- MIAMI - FLORIDA LARGE MISSILE IMPACT RESISTANT SWIFTENIA SERIES CASEMENT WINDOW MIAMI-DADE COUNTY PRODUCT APPROVED"

- 4- LOADS: DESIGNED LOAD CALCULATED BASED ON THE ASCE 7-10 AND PROVIDED BY A PROFESSIONAL ARCHITECT OR ENGINEER FOR EACH SPECIFIC PROJECT. THE CALCULATED DESIGNED PRESSURE MUST NOT EXCEED THE ALLOWABLE PRESSURES HERE IN SPECIFIED. THE DESIGN PRESSURES, AS DETERMINED FROM ASCE 7-10, ARE TO BE MULTIPLE BY 0.6.
- 5- MATERIAL: ALL WOOD MATERIAL TO BE FABRICATED FROM KILN DRIED MAHOGANY.
- G- FASTENERS: ASSEMBLY SCREWS AND ANCHORS SHALL BE AS SPECIFIED IN THE CURRENT SET OF DRAWINGS. INSTALLATION AND LOADS AS PER THIS APPROVAL.
- 7- USE: IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR, ARCHITECT OR ENGINEER OF RECORD TO VERIFY THE FOLLOWING: 7.1 - THE STABILITY OF THE STRUCTURE WHERE THE SHUTTER IS TO
- BE ATTACHED INSURING PROPER ANCHORAGE. 7.2- THE SITE SPECIFIC PROJECT CRITERIA, SUCH AS BUT NOT LIMITED TO.WNDLOADS, LOCAL CODE REQUIREMENTS, DESIGNED PRESSURES ETC.
- 7.3- THAT THIS APPROVAL IS ADEQUATE TO THE SPECIFIC PROJECT.

TABLE OF CONTENTS:

SHEET	CONTENTS
I OF 7	TYPICAL SINGLE ELEVATIONS, DESIGN RATING, GENERAL NOTES
2 OF 7	TYPICAL PAIR ELEVATIONS, DESIGN RATING
3 OF 7	TYPICAL ANCHORAGE LAY-OUT
4 OF 7	TYPICAL CROSS SECTIONS AND CLADDING OPTIONS
5 OF 7	HARWARE LAY-OUT
6 OF 7	ANCHORAGE DETAIL, PRODUCT ASSEMBLY
7 OF 7	PRODUCT COMPONENTS AND BILL OF MATERIALS

TYPICAL SINGLE ELEVATIONS



FULL ARCH

CONFIGURATION

DESIGNED PRESSURE RATING Pd= ± 75 PSF

1/2 ARCH

CONFIGURATION

MAXIMUM FRAME SIZES:

SQUARE

CONFIGURATION

FINISHED WIDTH: FW= 39 1/2" FINISHED HEIGHT: FH= 123"

MAXIMUM CLADDING SIZES:

1/2" GLASLAM SAFETY-PLUS II IMPACT GLASS DLO: 25 3/4" X 103 1/2" 1 1/2" MAHOGANY SOLID WOOD PANEL DLO: 25 3/4" X 75 1/2"

> LEGEND FH - FINISHED HEIGHT FW - FINISHED WIDTH DLO- DAY LIGHT OPENING DPH - WINDOW PANEL HEIGHT DPW - WINDOW PANEL WIDTH

WOOD TYPE: VERNACULAR NAME: TRUE MAHOGANY SCIENTIFIC NAME: SWIETENIA MACROPHYLLA G. KING FAMILY: MELIACEAE MINIMUM SPECIFIC GRAVITY: 0.45

LITE WITH PANEL

CONFIGURATION

GLASS TYPE: 1/2" Laminated made of two 3/16" anneal lites PLUS GLASIAM SAFETY-PLUS II INTERLAYER AS PER **CURRENT NOA**

ROATAN MAHOGANY USA, INC

MANUFACTURER:

4004C AURORA STREET CORAL GABLES, FL 33146 PHONE: (305) 774-5999 FAX: (305) 774-0083

PRODUCT:

MAHOGANY CASEMENT WINDOWS SWIETENIA SERIES

CASEMENT WINDOW LARGE & SMALL MISSILE IMPACT

ENGINEERING:

ENGCO INC. CABILG

5595 ORANGE DR. 201 DAVIE, FL. 33314 Tel.: (954) 585-0304 ENGCO@AOL.COM



AUG 2 6 2015 Engineer Seal Pedro De Figueiredo - PE 52609

MIAMI-DADE BCCO:

PRODUCT REVISED as complying with the Florida Building Code 15-0921.09 NOA-No.

Expiration Date 08/08/2019


Miami-Dade Product Control

DATE: 08/26/2015 SCALE: NA DESIGN BY: PPMF


> SHEET LOE 7

DRAWING #: 15-254


TYPICAL PAIR ELEVATIONS



TYPE 5
SPLIT PANEL CONFIGURATION



TYPE G ARCH CONFIGURATION



TYPE 7
SQUARE CONFIGURATION

DESIGNED PRESSURE RATING
Pd= ± 75 PSF

MAXIMUM FRAME SIZES:

FINISHED WIDTH: FW= 75 1/2"

FINISHED HEIGHT: FH= 123"

MAXIMUM CLADDING SIZES:

1/2" GLASLAM SAFETY-PLUS II IMPACT GLASS

DLO: 25" X 1 O3 3/4"

1 1/2" MAHOGANY SOLID WOOD PANEL

DLO: 25" X 75 1/2"

MANUFACTURER:

ROATAN MAHOGANY USA, INC

4004C AURORA STREET CORAL GABLES, FL 33146 PHONE: (305) 774-5999 FAX: (305) 774-0083

PRODUCT:

MAHOGANY CASEMENT WINDOWS

SWIETENIA SERIES CASEMENT WINDOW LARGE & SMALL MISSILE IMPACT

ENGINEERING:

ENGCO INC. CABILG

5595 ORANGE DR. 201 DAVIE, FL. 33314 Tel.: (954) 585-0304 ENGCO@AOL.COM

NO 52609

* STATE OF CONAL ENGINEERS ON AL 2015

AUG 2 6 2015

Engineer Seal
Pedro De Figueiredo - PE 52609

MIAMI-DADE BCCO:

PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 15-0921.09


Expiration Date 08/08/2019


By Miami Dade Product Control


DATE: 08/26/2015 SCALE: NA DESIGN BY: PPMF

> SHEET 2 OF 7


DRAWING #: 15-254









TYPICAL ANCHORAGE DETAILS




OPTION I
FRAME WITH MAXIMUM 1/4" PT WOOD SHIM
1/4" ULTRACONS BY ELCO WITH 1 1/4" MIN.
EMBEDMENT INTO MASONRY
(SEE SHEET 3 OF 7 FOR ANCHORS LAY-OUT)




OPTION 2
FRAME WITH MAXIMUM 1/4" PT WOOD SHIM AND
I"X PT CONT. WOOD SPACER
I/4" ULTRACONS BY ELCO WITH | 1/4" MIN.
EMBEDMENT INTO MASONRY
(SEE SHEET 3 OF 7 FOR ANCHORS LAY-OUT)



OPTION 3
FRAME WITH MAXIMUM 1/4" PT WOOD SHIM
AND 2"X PT CONT. WOOD BUCK BY OTHERS
#14 SS WOOD SCREWS OR 1/4" ULTRACONS WITH
1 1/2" MIN. EMBEDMENT INTO WOOD (SG=.55)
(SEE SHEET 3 OF 7 FOR ANCHORS LAY-OUT)



OPTION 4
FRAME WITH MAXIMUM 1/4" PT WOOD SHIM
1/4"-20 HWH DRILFLEX SELF DRILLING SCREWS BY
ELCO INTO MIN.1/8" A36 STEEL
(SEE SHEET 3 OF 7 FOR ANCHORS LAY-OUT)



MANUFACTURER:

ROATAN MAHOGANY USA, INC

4004C AURORA STREET CORAL GABLES, FL 33146 PHONE: (305) 774-5999 FAX: (305) 774-0083


PRODUCT:

MAHOGANY
CASEMENT
WINDOWS
SWIETENIA SERIES
CASEMENT WINDOW
LARGE & SMALL MISSILE IMPACT

engineering:

ENGCO INC. CABITE

5595 ORANGE DR. 201 DAVIE, FL. 33314 Tel.: (954) 585-0304 ENGCO@AOL.COM



MIAMI-DADE BCCO:

PRODUCT REVISED
as complying with the Florida
Building Code
NOA-No. 15-0921.09

Expiration Date 08/08/2019

By Miami-Dage Product Control

DATE: 08/26/2015 SCALE: NA DESIGN BY: PPMF

> SHEET 6 OF 7

DRAWING #: 15-254

MANUFACTURER: PRODUCT COMPONENTS AND BILL OF MATERIALS ROATAN MAHOGANY SASH PARTS CLADDING FRAME PARTS USA, INC D5 MID RAIL Ď3 4004C AURORA STREET . EXTERIOR GLI- 1/2" GLASSLAM SAFETY-PLUS II CORAL GABLES, FL 33146 MOULDING LAMINATED GLAZING MATERIAL BOTTOM RAIL PHONE: (305) 774-5999 FAX: (305) 774-0083 1. 25 O. 13" POLYURETHANE ~ PRODUCT: 3/16 3/16* ANNEAL ANNEAL **MAHOGANY** GLASS GLASS CASEMENT WINDOWS SWIETENIA SERIES 3. 88 -CASEMENT WINDOW LARGE & SMALL MISSILE IMPACT ENGINEERING: FI- JAMBS AND HEADER ENGCO INC. CABILG D4 5595 ORANGE DR. 201 INTERIOR DAVIE, FL. 33314 MOULDING Tel.: (954) 585-0304 ENGCO@AOL.COM GL2- 1 3/4" SOLID 6, 50 MAHOGANY PANEL 1, 33 2.50 -2. 25 0. 95 KADE OF THREE PANEL SIZE HANDGANY PLIES D2 STILES AND TOP RAIL ONAL ENG AUG 2 6 2015 - 1.50-- 1.00 ---DG Engineer Seal INACTIVE LEAF Pedro De Figueiredo - PE 52609 F2- THRESHOLD **ASTRAGAL** MIAMI-DADE BCCO: 2, 25 0.50 0.38 MADE OF THREE 🚗 MANDGANY PLIES PRODUCT REVISED as complying with the Florida Bullding Code **BILL OF MATERIALS GASKETS** 15-0921.09 NOA-No. ITEM# DE5CRIPTION REMARKS **D7** MAHOGANY WOOD . 50 2,25'X TO DΙ BOTTOM RAIL Expiration Date 08/08/2019 **ACTIVE LEAF** MAHOGANY WOOD TOP RAIL **‡** STILES 2.25'X 4.75' D2 **ASTRAGAL** D3 EXTERIOR MOULDING 1.50'X 1.25' MAHOGANY WOOD -- 2, 25**′** ---MAHOGANY WOOD D4 INTERIOR MOULDING Miami-Datte Froduct Control 1.50'X 1.375" MAHOGANY WOOD 2.25 X 6.25 D5 MID RAIL MAHOGANY WOOD D6 INACTIVE ASTRAGAL 3.50°X 1.50° KADE OF THREE --20 MAHOGANY WOOD 07 ACTIVE ASTRAGAL 2.13 X 1.50 HAHDGANY PLIES 1. 00 BY GLASSLAM ĞĻJ IMPACT GLASS 1/2" LAMINATED က GL2 SOLID PANEL 1.75° THICK MAHOGANY WOOD DATE: 08/26/2015 MAHOGANY WOOD Fi JAMB AND HEADER 1,75'X6.50' SCALE: NA MAHOGANY WOOD F2 .875'X6.50' Gl PEMKO V80DS VINYL DESIGN BY: PPMF ĞĪ BOTTOM RAIL GASKE 2.25"XO.5" G2 **BOTTOM RAIL** G2 SCHEGEL QDS 650 0.65'XO.58' FRAME SEAL QDS 650 SCHLEGEL GASKET WEATHERSTRIP PEMKO V80DS SHEET DRAWING #: --- 1. 50 ---7 OF 7 15-254